PET RELIEF ROOM, DESIGN INTENT

1.01 DESIGN LAYOUT

- A. Pet Relief Rooms will be located behind the airport security screening area in each Terminal.
- B. Pet Relief Rooms will be accessible from the main public circulation path.
- C. Pet Relief Rooms will not have a water closet, urinal or diaper changing surface.

1.02 MECHANICAL

A. Pet Relief Rooms will have 15 air changes per hour minimum.

1.03 PLUMBING

- A. To the extent possible, water shut-off valves, temperature control valves, electrical transformers, etc. will be located within 30 horizontal inches of a wall or ceiling access panel.
- B. Alternative location of access panel will be located under the lavatory.

1.04 LIGHTING

A. Lighting will match the Public Restrooms as described in the Public Restroom, Design Intent.

1.05 ACCESSORIES

- A. The Pet Relief Room will have the following accessories (in compliance with ADA requirements):
 - i. Lavatory
 - ii. Soap dispenser
 - iii. Mirror
 - iv. Paper Towel dispenser
 - v. Paper Towel waste receptacle
 - vi. Aluminum DogiPot Pet Station (#1003-L) that includes dog bags and waste receptacle with lid and mobile mounting base
 - vii. Hose bib
 - viii. Synthetic grass pet relief area

1.06 WALLS

- A. Where feasible, metal stud partitions will be installed on a 6" high concrete curb.
- B. Walls will have waterproofing membrane extend full height from floor to ceiling.
- C. Wall field tile will be full height ceramic tile laid up in a horizontally balanced and consistent pattern from corner to corner and bottom to top. Horizontal stack bond pattern is preferred. Wall field tile will start with a full tile above the wall base tile. Tile color will be '**White**'. Tile grout will be epoxy, color '**White**'.
- D. Stainless steel flush corner guards will match the Public Restrooms as described in the Public Restroom, Design Intent.

1.07 FLOORS

- A. Floor finish will have positive slope to floor drain(s).
- B. All floors with have tile finish. Tile color will be through body '**Medium Grey**'. Tile grout will be epoxy, color to match tile.
- C. Tile cove base will be provided and match floor tile. Non-tile cove bases and cove strips are not acceptable.
- D. Pet relief area with have synthetic grass inserted over tiled floor.
- E. Pet relief area will have passenger activated rinsing system operable by a push button. Rinsing system can be sprinkler(s) in grass area, or soaking system under grass area.

1.08 CEILINGS

- A. Ceiling heights will be 9'-0" minimum above finished floor.
- B. Porous ceiling materials are not acceptable.
- C. Ceiling will be cement plaster or water resistant gypsum board.
- D. All ceilings will be painted white.
- E. All access panels, registers and grills will be painted to match ceiling.

END OF SECTION